



DIMENSIONS

UNIT: mm

SIZE		d	d1	H	L	S	MASS (Kg)	Q'ty
A	B							
10	3/8	Rc 3/8	13	39	53	23	0.24	
15	1/2	Rc 1/2	13	39	60	28	0.31	
20	3/4	Rc 3/4	19	45	70	35	0.45	
25	1	Rc 1	25	52	80	43	0.70	
32	1 1/4	Rc 1 1/4	32	62	92	52	1.04	
40	1 1/2	Rc 1 1/2	38	67	102	59	1.36	
50	2	Rc 2	50	79	122	72	2.35	
65	2 1/2	Rc 2 1/2	65	91	150	87	3.52	
80	3	Rc 3	80	102	165	102	4.69	



BODY MARKING

18	PLUG	C 3 6 0 4 B D	
17	HINGE PIN	C 3 6 0 4 B D	
4	DISC	C 3 7 7 1 B E	
2	CAP	C 3 7 7 1 B E	
1	BODY	C A C	Cast bronze
No.	PART	MATERIAL	NOTE

FACE TO FACE OR END TO END  
MAKER'S STANDARD

END CONNECTION  
JIS B0203

WALL THICKNESS  
MAKER'S STANDARD

PRESSURE TEST  
MAKER'S STANDARD

CLASS 125  
CAST BRONZE SCREWED END  
SWING CHECK VALVE

APP'D	K.Kobayashi	FIGURE	PRODUCT CODE		
CHK'D	H.Fuseya	125-BNS-N	234		
CHK'D	M.Mochizuki	DRAWING No.	△		
PREP'D	K.Kohama	08L20000	MARK	DATE	BY
DATE	JUL.31.'15				



**Toyo Valve Co., Ltd.**